



TIMKEN AXLE CORP.

0.394 Inch | 10 Millimeter x 1.181 Inch | 30 Millimeter x 0.563 Inch | 14.3 Millimeter SKF 3200 A-2RS1TN9/C3 Angular Contact Ball Bearings



3200 A-2RS1TN9/C3 Bearing 2D drawings and 3D CAD models

Bearing No. 3200 A-2RS1TN9/C3

| | |
|---------------------------------|--|
| Category | Angular Contact Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.056 |
| EAN | 7316573930747 |
| Product Group | B00152 |
| Enclosure | 2 Seals |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Polyamide |
| Contact Angle | 30 Degree |
| Internal Clearance | C3-Loose |
| Number of Bearings | 1 (Single) |
| Inch - Metric | Metric |
| Long Description | 10MM Bore; 30MM Outside Diameter; 14.3MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot; |



TIMKEN AXLE CORP.

| | |
|----------------------------------|---|
| | No Snap Ring; C3-Loose; Polyamide Cage; 30 Degree; 1 (Sin |
| Other Features | NBR Contact Seal Glass Fibre Reinforced Cage |
| Category | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 3200 A-2RS1TN9/C3 |
| Weight / LBS | 0.1238 |
| D | 1.181 Inch 30 Millimeter |
| d | 0.394 Inch 10 Millimeter |
| B | 0.563 Inch 14.3 Millimeter |
| bore diameter: | 10 mm |
| operating temperature range: | -40 to +210 ° F |
| outside diameter: | 30 mm |
| cage material: | Fiberglass Reinforced Nylon |
| overall width: | 0.5625 in |
| outer ring width: | 14.3 mm |
| row type & fill slot: | Double-Row Non-Fill Slot |
| maximum rpm: | 17000 RPM |
| internal clearance: | C3 |
| finish/coating: | Uncoated |
| closure type: | Double Seal |
| precision rating: | Not Rated |
| radial dynamic load capacity: | 7.61 kN |
| fillet radius: | 0.6 mm |
| radial static load capacity: | 4.3 kN |
| | |



TIMKEN AXLE CORP.

series:

32