



TIMKEN AXLE CORP.



2.559 Inch | 65 Millimeter x 4.724 Inch | 120 Millimeter x 0.906 Inch | 23 Millimeter SKF NU 213 ECM/C4 Cylindrical Roller Bearings

Bearing No. NU 213 ECM/C4

NU 213 ECM/C4 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	1.234
EAN	7316576621666
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C4-Extra Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	65MM Bore; Straight Bore Profile; 120MM Outside Diameter; 23MM Width;



TIMKEN AXLE CORP.

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C4-Extra Loose
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 213 ECM/C4
Weight / LBS	2.718
d	2.559 Inch 65 Millimeter
B	0.906 Inch 23 Millimeter
D	4.724 Inch 120 Millimeter
bore diameter:	65 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	120 mm
maximum rpm:	6700 RPM
overall width:	23 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C4
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	23 mm



TIMKEN AXLE CORP.

operating temperature range:	Maximum of +300 ° F
fillet radius:	1.5 mm
dynamic load capacity:	122 kN
series:	NU2
static load capacity:	118 kN