



TIMKEN AXLE CORP.



2.559 Inch | 65 Millimeter x 5.512 Inch | 140 Millimeter x 1.89 Inch | 48 Millimeter SKF NJG 2313 VH/C3 Cylindrical Roller Bearings

Bearing No. NJG 2313 VH/C3

NJG 2313 VH/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	3.621
EAN	7316570788150
Product Group	B04144
Bore Profile	Straight
Cage Material	None
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - One Side
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	No
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Full Complement 1 Rib Inner Ring 2 Rib Outer Ring
Long Description	65MM Bore; Straight Bore Profile; 140MM Outside Diameter; 48MM Width;



TIMKEN AXLE CORP.

	RBEC 1 ISO P0; Single Row; Inner Ring - One Side Separable; No Snap Ring; Relubricatable; C3-Loose Internal Clearance; No Retain
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NJG 2313 VH/C3
Weight / LBS	7.976
d	2.559 Inch 65 Millimeter
D	5.512 Inch 140 Millimeter
B	1.89 Inch 48 Millimeter
bore diameter:	65 mm
static load capacity:	360 kN
outside diameter:	140 mm
precision rating:	Not Rated
overall width:	48 mm
maximum rpm:	2400 RPM
flanges:	(2) Outer Ring, (1) Inner Ring
cage material:	No Cage
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	48 mm
ring separation:	Non-Separable
fillet radius:	2 mm
operating temperature	Maximum of +300 ° F



TIMKEN AXLE CORP.

range:	
series:	NJG23
dynamic load capacity:	303 kN